## United States Patent [19]

[54] CAM OPERATED INVERTER BYPASS

## **Panuce**

[58] Field of Search ..

[56]

[11] Patent Number:

5,721,449

**Date of Patent:** [45]

6/1979 Wiktor

2/1983 Kruger ..

3/1985 Alsch .

4,423,336 12/1983 Iverson et al.

8/1983 Schell et al.

2/1988 Heng et al.

7/1988 Thomson

7/1989 Schaeffer .

9/1991 Spanio ...

6/1990 Minoura et al. .

6/1991 Bassett et al. .

1/1992 Smith et al. .

4/1993 Smith et al. .

10/1981 Kovatch et al. .

4,157,461

4,295,054

4,371,820

4,398,097

4,503,412

4,724,287

4,760,278

4,851,620

4,937,403

5,023,469

5,048,366

5,081,367

5,200,586

Feb. 24, 1998

200/18

307/64

200/14 X

200/14

74/567

307/64

200/16 A

200/50.32

200/243

200/50.21

307/64

[O .]	SAFETY SWITCH		
[75]	Inventor:	Donald G. Pannee. South Barrington. III.	
[73]	Assignee:	Advance Controls, Inc., Wood Dale,	
[21]	Appl. No.: 603,657		
[22]	Filed:	Feb. 20, 1996	
[51]	Int. CL <sup>6</sup> .	H01H 19/60; H01H 21/80; H02J 9/00	
[52]	U.S. CL _	200/14; 200/16 A; 200/18; 307/64	

Primary Examiner—J. R. Scott	
Attorney, Agent, or Firm-Bullwinkel	Partners, Ltd.

**ABSTRACT** [57]

5,075,517 12/1991 Spanio

5.278,369 1/1994 Spanio .

U.S. PATENT DOCUMENTS						
2,326,070	8/1943	Sachelchun et al	307/64			
3,251,956	5/1966	Rasor et al.	200/14			
3,260,803	7/1966	Moroishi	200/6 B			
3,614,363	10/1971	Fujita	200/303			
3,614,461	10/1971	Spear et al.	307/64			
3,753,069	8/1973	Newton	318/440			
3,987,268	10/1976	Macda et al	200/6 B X			
4,154,996	5/1979	Amold	200/243			

References Cited

200/14, 16 A, 17 R, 18, 558-573; 310/68 R-71;

200/4, 6 B, 6 BB.

An inverter by pass safety switch for rerouting electrical power either through or around AC variable frequency inverter drives during electrical disturbances, thus allowing a motor to continue operation. The switch works in a mechanical fashion, and comprises a contact block containing electrical contacts and cams operably connected to the contacts and mounted on a shaft that can be turned by an operator. The cams are shaped and mounted on the shaft in such a way to provide a desired switching pattern when the shaft is manually rotated.

3 Claims, 3 Drawing Sheets

